Technical Data Sheet



PA412 SERIES POWER TAKE-OFF

Deep Reach High Torque 8 Bolt Side Mounted PTO

The 412 series is designed for the left opening of certain Hino transmissions with an 8 bolt opening. It is a heavy duty deep reach design.

Suits:

Hino LX06S transmissions. (Refer to the eGuide Configurator on www.hydreco.com for confirmation and details)


Product Features

- Output Speeds 65.3 to 87.6% of Engine Speed (Transmission Dependant)
 For very high torque at the output.
- Wide Variety of Outputs
 To suit many vehicle configurations.
- Constant Mesh Gears
 For longer life.
- Heavy Duty Tapered Roller Bearings
 For long life and better support for the idler gear.





Technical Data Sheet



PTO DESIGNATION CODES 412 Series PA 412 MK L23 A 08 * Identifier PA = PTO Side Mount **PTO Series** 412 Gear Type MK L = Left side of transmission 2 = Selector to bottom / Bias to top 3 = Front to centre (Position of gear in transmission) **Engagement Type** A = Air **Output Type** 08 = 8T Powauto Hydraulic Spline 09 = 14T 12/24 30° Spline + 35 x 60 Flange 10 = 14T 12/24 30° Spline + 1310 Flange 11 = 14T 12/24 30° Spline + 1410 Flange 13 = 13T SAE B Hydraulic Spline + SAE B Pump Mount 23 = 8T Ø36 DIN 5462 Spline - Female and DIN Mount 41 = 3B UNI Pump Mount Other outputs available on request, subject to MOQ. Manufacturers Code 4 A = With Pressure Switch B = With Mounting Kit C = With Mounting Kit & PTO Control Kit

Technical Specifications Ratings & Service Parts		
Torque	Nm / ft.lb	355 / 261
Power @ 500 rpm	kW / hp	18.5 / 24.8
Power @ 1000 rpm	kW / hp	37.0 / 49.7
Output Shaft Rotation	73 3	Opposite To Engine
Approximate Bare Mass	kg / lb	15.0 / 33.0
Mounting Kit		MK1167
Mounting Gasket Kit		GK017
Seal Kit		SK065A
Bearing Kit		BK065A


Note: For full details refer to the owners manual or the eGuide configurator found at www.hydreco.com/markets/transport

POWAUTO

Despaying Brown

HYDRECO.





Doc: PA412-03/17

www.hydreco.com